

GENERAL

Standard	EN61010-1 EN61010-2-201 EN61131-2
Dimensions (W × H × D)	72x90x62mm
Weight	250g
Mounting	Top hat rail EN50022, 35mm

ENVIRONMENTAL CONDITIONS

Operating ambient temperature	0°C – 55°C
Relative humidity – non-condensing	80 % for temp. up to 31 °C, decreasing linearly to 50 % relative humidity at 55 °C
Pollution Degree	PD2
Altitude	up to 2000m AMSL
Vibration (5 ≤ f ≤ 9 Hz)	1,75 mm amplitude sinus 3,5 mm amplitude random
Vibration (9 ≤ f ≤ 150 Hz)	0,5 g acceleration sinus 1,0 g acceleration random
Transport and Storage	-20°C – +70°C 10 to 90% no condensation Altitude 3000m AMSL
Shock response	15g, 11ms half sinus all 3 axes

I/O

Supply voltage	12V or 24V
USB (Power for programming only)	USB-B, 2.0
Ethernet	RJ45, 10/100Mbps
RS485 (no termination inside)	250kb
Inputs, no galvanic insulation	12
Common analog/digital	10
Fixed digital, ext. Interrupt usable	2
Digital Outputs, no galvanic insulation	12
Relay Outputs, galvanic insulation	10

TERMINAL CAPACITIES

Relay Output, Power Input	2,5mm ² (24-12AWG)
Strip length	6-7mm
Max. tightening torque	0,5Nm
Digital, Analog Input Output	1,5mm ² (30-16AWG)
Strip length	5-6mm
Max. tightening torque	0,2Nm

PROTECTION

ESD HBM Class 0	Contact discharge: ±4kV Air discharge: ±8kV
Supply input over current protection	Internal Fuse 20A
Relay Output	External Fuse required
Digital Output	Overload, short circuit, ESD
Signal Input	Overvoltage, ESD

ELECTRICAL CHARACTERISTICS

	Condition	Value
Supply voltage	12V range	10,2V – 15,0V
	24V range	20,4V – 30,0V
Signal input low level	12V range	0V – 3,6V
	24V range	0V – 7,2V
Signal input high level	12V range	9V – 13,2V

Analog signal input	24V range	18V – 26,4V
	12V range	0 – 13,2V
Signal input current	24V range	0 – 26,4V
Signal output low level	max. current	< 3mA
	12V range	0V – 2,4V
Signal output high level	24V range	0V – 4,8V
Signal output – PWM functionality	Duty cycle	Vin – 10%
Relay output, Contact rating	Resistive Load	5% - 95%
	max. current	6A 250V AC / 30V DC
Common Relay terminal	coil to contact	6A
Galvanic insulation	Duty cycle	3000VAC 1min
Relay ON in case of PWM functionality		> 30%

LED SIGNALIZATION

Power LEDs coding	Color of power LED
only USB powered	12V green, 24V green
input voltage out of range	12V orange, 24V orange
input voltage 10.2V – 15,0V	12V green, 24V orange
input voltage 20.4V – 30,0V	12V orange, 24V green
input voltage < 7V	both LEDs off
Device in reset state	Reset LED yellow
Device in run state	Reset LED off
Signal input at high (logic 1) level	Corresponding LED green
Signal input at low (logic 0) level	Corresponding LED off
Signal input in use as analog input	Corresponding LED green on when input level reach high (logic 1) state
Signal/Relay output set to active	Corresponding LED green
Signal/Relay output set to inactive	Corresponding LED off

PHYSICAL DIMENSIONS

